



ISOMETRIC VIEW

NOTES: UNLESS OTHERWISE SPECIFIED.

1. ALL DIMENSIONS ARE IN DECIMAL INCHES.
2. PRECAST MATERIALS AND MANUFACTURING METHODS SHALL CONFORM TO ASTM C-478.
3. CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH F_C = 4000 PSI AT 28 DAYS.
4. THE PORTLAND CEMENT USED IN THE PRECAST SECTIONS SHALL MEET THE REQUIREMENTS OF TYPE II/V HIGH SULFATE RESISTANT CEMENT IN ACCORDANCE WITH ASTM C-150.
5. RING AND COVER SHALL BE GREY CAST IRON CONFORMING TO ASTM A-48 CLASS 35B.
6. RING AND COVER A-1254 "CITY OF THOUSAND OAKS SEWER".
7. PRE-CAST JOINTS SHALL BE SEALED USING MASTIC.

REGON PRODUCTS			
Phone (805) 527-0841 Fax (805) 584-0769			
TITLE		MANHOLE, 48 DIA, SHAFT, 24 RING & COVER-THOUSAND OAKS	
APPROVED BY	DATE	APPROVED BY	DATE
DRAWN BY	DATE	MODEL NO.	SH 1 OF 1
F. ANSALDI	12/2/2005	MH4824TO	